

# SÜDWEST Entlacker

Ref. 130000007289/

Rev. no. 1.0

Revision Date 15.10.2018 Print Date 23.10.2018

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Trade name SÜDWEST Entlacker

1.2 Relevant identified uses of the substance or mixture and uses advised against

Paint remover

Uses advised against This information is not available.

1.3 Details of the supplier of the safety data sheet

SÜDWEST Lacke + Farben GmbH & Co.KG

Iggelheimer Str. 13 D - 67459 Böhl-Iggelheim Telephone: +49 6324/709-0

Telefax: +49 6324/709-175

'n

www.suedwest.de

E-mail address of person responsible for the SDS

European Union

sdb@suedwest.de

**1.4 Emergency telephone number** European Union Phone: +44 (0)1235 239 670

## **SECTION 2: HAZARDS IDENTIFICATION**

## 2.1 Classification of the substance or mixture

## Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H302: Harmful if swallowed.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

#### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word	Warning

Hazard statements H302 Harmful if swallowed.
H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary P102 Keep out of reach of children. statements Prevention:

P280 Wear protective gloves/ protective

clothing/ eye protection/ face protection.

Response:

P301 + P312 IF SWALLOWED: Call a POISON

CENTER/doctor if you feel unwell.

P302 + P352 IF ON SKIN: Wash with plenty of soap

and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with

water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

Disposal:

P501 Contents/container to be disposed of

through approved disposal contractor or

taken to municipal collection point.

Hazardous components which must be listed on the label:

1-butylpyrrolidin-2-one

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2 Mixtures

#### **Hazardous components**

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (% w/w)
1-butylpyrrolidin-2- one	3470-98-2 222-437-8 01-2120062728-48- XXXX	Acute Tox.4; H302 Skin Irrit.2; H315 Eye Irrit.2; H319	≥ 10 - < 25
formic acid%	64-18-6 200-579-1 01-2119491174-37- XXXX	Flam. Liq.3; H226 Eye Dam.1; H318 Skin Corr.1A; H314 Acute Tox.3; H331 Acute Tox.4; H302 Note B	< 2,5

For explanation of abbreviations see section 16.

## **SECTION 4: FIRST AID MEASURES**

## 4.1 Description of first aid measures

General advice When symptoms persist or in all cases of doubt seek

medical advice.

Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical

advice.

Inhalation Move to fresh air in case of accidental inhalation of vapours

or decomposition products. Keep patient warm and at rest.

If breathing is irregular or stopped, administer artificial

respiration.

If symptoms persist, call a physician.

Skin contact Take off contaminated clothing and shoes immediately.

Wash skin thoroughly with soap and water or use

recognized skin cleanser.

Do NOT use solvents or thinners. If skin irritation persists, call a physician.

Eye contact In case of eye contact, remove contact lens and rinse

immediately with plenty of water, also under the eyelids, for

at least 15 minutes. Seek medical advice.

Ingestion Rinse mouth with water.

If swallowed, seek medical advice immediately and show

## SÜDWEST Entlacker

this container or label.

Keep at rest.

Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat symptomatically.

No information available.

## **SECTION 5: FIREFIGHTING MEASURES**

5.1 Extinguishing media

Suitable extinguishing

media

CO2, extinguishing powder or water spray. Fight larger fires

with water spray or alcohol resistantfoam.

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture Fire may cause evolution of:

Carbon monoxide Carbon dioxide (CO2) Nitrogen oxides (NOx)

Exposure to decomposition products may be a hazard to

Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

Fight fire with normal precautions from a reasonable

distance.

Additional advice Fire residues and contaminated fire extinguishing water

must be disposed of in accordance with local regulations.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

6.1 Personal precautions, protective

equipment and

emergency procedures

Remove all sources of ignition. Ensure adequate ventilation.

Do not breathe vapour.

Prevent unauthorized access.

6.2 Environmental

precautions

The product should not be allowed to enter drains, water

courses or the soil.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and

material for

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth,

containment and cleaning up

vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

Clean with detergents. Avoid solvents. Clean contaminated surface thoroughly.

Dispose of contaminated material as waste according to

item 13.

6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8.

## **SECTION 7: HANDLING AND STORAGE**

## 7.1 Precautions for safe handling

Advice on safe handling Comply with the statutory regulations on health and safety at

work.

Avoid formation of aerosol.

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour

concentration higher than the occupational exposure limit values.

The product should only be used in areas from which all naked lights and other sources of ignition have been

excluded.

All metal parts of the mixing and processing equipment must

be earthed.

Operators should wear antistatic footwear and clothing. No

sparking tools should be used.

Hygiene measures Do not breathe spray, vapour.

Take off immediately all contaminated clothing. Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

After washing hands, replenish lost skin oil by means of oily

skin ointment.

When using do not eat, drink or smoke.

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container.

Keep container tightly closed. Never use pressure to empty:

container is not a pressure vessel. Nosmoking.

Prevent unauthorized access.

Containers which are opened must be carefully resealed

and kept upright to prevent leakage. Protect from frost, heat and sunlight.

## SÜDWEST Entlacker

Advice on protection against fire and

Vapours may form explosive mixtures with air.

Take measures to prevent the build up of electrostatic

Vapours are heavier than air and may spread along floors.

charge.

Advice on common

storage

explosion

Keep away from combustible materials.

Keep away from food, drink and animal feedingstuffs. Keep away from oxidizing agents and strongly acid or

alkaline materials.

7.3 Specific end use(s) For further information, see also Technical Data Sheet for

the product.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

## Exposure limit(s)

Components		CAS-No.
Basis	Type:	Control
		parameters
formic acid%		64-18-6
2006/15/EC	Limit Value - eight hours	9 mg/m <sup>3</sup>
2006/15/EC	Limit Value - eight hours	5 ppm
Additional advice:	Indicative	

The lists that were valid during the creation were used as basis.

## 8.2 Exposure controls

### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should beachieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates solvent vapour below the occupational exposure limit values, suitable respiratory - protection must be worn. Washing facilities / water for rinsing eyes and skin should be available.

## Individual protection measures, such as personal protective equipment

a) Eye/face protection Safety glasses with side-shields conforming to EN166

b) Skin protection

Hand protection Break through time: 480 min Minimum thickness: 0,4 mm

> e.g. KCL 897 "Butoject®" - butyl rubber protective glove -(Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300,

kcl-uk@kcl.de)or equal.

Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.

The selected protective gloves have to satisfy the

specifications of EU Directive 89/686/EEC and the standard

EN 374 derived from it.

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different

from one producer to the other.

Body Protection Preventive skin protection

Long sleeved clothing

Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthehic fiber. All parts of the body should be washed after contact.

c) Respiratory protection When workers are facing concentrations above the

occupational exposure limit values they must use

appropriate certified respirators.

In case of inadequate ventilation wear respiratory protection.

Do not breathe in dust when grinding.

Combination filter A-P2

Respiratory protection complying with EN 14387.

#### **Environmental exposure controls**

General advice The product should not be allowed to enter drains, water

courses or the soil.

If the product contaminates rivers and lakes or drains

inform respective authorities.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1 Information on basic physical and chemical properties

Appearance paste

Colour beige

Odour characteristic

Odour Threshold No data available

pH ca. 5 (20 °C)

Concentration: 10 g/l

Melting point/freezing point 

No data available

Initial boiling point and No data available

# **SÜDWEST Entlacker**

boiling range

Flash point 100 °C

Method: Pensky-Martens closed cup

Evaporation rate not applicable

Flammability (solid, gas) not applicable

Upper explosion limit / 47,6 %(V)

Lower explosion limit / 0,95 %(V)

Lower flammability limit Lower explosion limit

Vapour pressure 42 mbar (20 °C)

Vapour density No data available

Density ca. 1,09 g/cm³ (20 °C)

Solubility(ies)

Water solubility partly soluble

Partition coefficient: n-

octanol/water

not determined

Auto-ignition temperature > 350 °C

Decomposition temperature

No data available

Viscosity

Viscosity, dynamic ca. 10.000 mPa.s

Viscosity, kinematic No data available

Explosive properties Not explosive

Oxidizing properties Not applicable

9.2 Other information

Flow time No data available

## **SECTION 10: STABILITY AND REACTIVITY**

## 10.1 Reactivity

# SÜDWEST Entlacker

No dangerous reaction known under conditions of normal use.

## 10.2 Chemical stability

Stable under normal conditions.

## 10.3 Possibility of hazardous reactions

Hazardous reactions No dangerous reaction known under conditions of

normal use.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid Direct sources of heat.

Strong sunlight for prolonged periods.

10.5 Incompatible materials

Materials to avoid Strong acids and strong bases

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition

products

Decomposition

temperature

No decomposition if stored and applied as directed.

No data available

## **SECTION 11: TOXICOLOGICAL INFORMATION**

## 11.1 Information on toxicological effects

**Acute toxicity Product:** 

Acute oral toxicity Acute toxicity estimate: 2.000 mg/kg

Method: Calculation method

Acute inhalation toxicity Acute toxicity estimate: > 20 mg/l

> Exposure time: 4 h Test atmosphere: vapour Method: Calculation method

Acute dermal toxicity Based on available data, the classification criteria are

not met.

**Components:** 

1-butylpyrrolidin-2-one:

Harmful if swallowed. Acute oral toxicity

formic acid...%:

Harmful if swallowed. Acute oral toxicity

# SÜDWEST Entlacker

Acute inhalation toxicity Toxic if inhaled.

Skin corrosion/irritation

**Product:** 

Causes skin irritation.

Components:

1-butylpyrrolidin-2-one:

Causes skin irritation.

formic acid...%:

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

**Product:** 

Causes serious eye irritation.

**Components:** 

1-butylpyrrolidin-2-one:

Causes serious eye irritation.

formic acid...%:

Causes serious eye damage.

Respiratory or skin sensitisation

**Product:** 

Based on available data, the classification criteria are

not met.

Germ cell mutagenicity

**Product:** 

Genotoxicity in vitro Based on available data, the classification criteria are

not met.

Carcinogenicity

**Product:** 

Based on available data, the classification criteria are

not met.

Reproductive toxicity

**Product:** 

Effects on fertility Based on available data, the classification criteria are

not met.

Developmental Toxicity Based on available data, the classification criteria are

not met.

# SÜDWEST Entlacker

# STOT - single exposure Product:

Based on available data, the classification criteria are

not met.

STOT - repeated exposure Product:

Based on available data, the classification criteria are

not met.

## **Aspiration toxicity**

## **Product:**

Based on available data, the classification criteria are not met.

## **Experience with human exposure**

## **Product:**

General Information Exposure to component solvent vapours concentration

in excess of the stated occupational exposure limit may

result in adverse health effects.

Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and

central nervous system. Symptoms and signs:
headache, dizziness, fatigue, muscular weakness,
drowsiness and in extreme cases loss of consciousness.
Long-term or repeated contact with the product leads to
degreasing of the skin and can cause nonallergenic

contact skin damage (contact dermatitis) and / or the resorption of substances.

Solvent sprays can cause irritation and reversible

damage to the eye.

# Further information **Product:**

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive

1272/2008. (See sections 2 and 3 for details).

## **SECTION 12: ECOLOGICAL INFORMATION**

## 12.1 Toxicity

#### **Product:**

Toxicity to fish No data available

## 12.2 Persistence and degradability

## **Product:**

# SÜDWEST Entlacker

Biodegradability No data available

#### 12.3 Bioaccumulative potential

**Product:** 

Bioaccumulation No data available

12.4 Mobility in soil

**Product:** 

Mobility No data available

12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment This substance/mixture contains no components

considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative

(vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

**Product:** 

Additional ecological

information

Do not allow product to enter into ground water, bodies

of water or sewage systems.

### **SECTION 13: DISPOSAL CONSIDERATIONS**

## 13.1 Waste treatment methods

Product The user is responsible for proper coding and marking of

any waste.

When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09 "Other Construction and

**Demolition Waste**"

Partial and residual quantities can be reused.

Fluid remains constitute hazardous waste and should not be poured into the sewage system. They should be taken to a

local waste disposal site.

systems.

Collect always evaporation water and for separating the solids it should run over a gravel bed or a sand catcher. Normally the waste water can be passed into the sewage

channels on consultation with the local authorities.

Waste key for the unused product

20 01 29\* detergents containing dangerous substances

# SÜDWEST Entlacker

(\*) hazardous waste in terms of the European directive 91/689/EEC

#### **SECTION 14: TRANSPORT INFORMATION**

#### 14.1 UN number

Not regulated as a dangerous good

## 14.2 UN proper shipping name

Not regulated as a dangerous good

## 14.3 Transport hazard class(es)

Not regulated as a dangerous good

## 14.4 Packing group

Not regulated as a dangerous good

## 14.5 Environmental hazards

Not regulated as a dangerous good

## 14.6 Special precautions for user

Remarks This information is not available.

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks Not applicable

## **SECTION 15: REGULATORY INFORMATION**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC

Directive 2010/75/EU 26,3 %

286,6 g/l

VOC

Directive 2004/42/EC

does not fall under Directive 2004/42/EC

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals Not applicable

Other regulations

Comply with the statutory regulations on health and safety at

work.

Take note of Dir 94/33/EC on the protection of young people

at work

Take note of Dir 92/85/EEC on the safety and health at work

of pregnant workers.

## 15.2 Chemical safety assessment

This information is not available.

## **SECTION 16: OTHER INFORMATION**

Changes from the previous version are indicated by markings in the left-hand margin.

The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.

#### **Full text of H-Statements**

H226 : Flammable liquid and vapour.

H302 : Harmful if swallowed.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H318 : Causes serious eye damage. H319 : Causes serious eye irritation.

H331 : Toxic if inhaled.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation

## SÜDWEST Entlacker

Flam. Liq. : Flammable liquids
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP -Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. -Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS -Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory: TRGS - Technical Rule for Hazardous Substances: TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

## **Further information**

Other information

The assessment was carried out in accordance with Article 6 (5) and Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

# SÜDWEST Entlacker

Department issuing MSDS REG\_EU / EN

sdb@suedwest.de